

No Corrosion, No Movement, No Water Ingress with LEAK KING®

By providing support to the roof sheets and adding rigidity to the overall roof structure, the LEAK KING® system prevents the indentations and loosening of fasteners that lead to leakage. When you use the LEAK KING® roof fixing system, you will not experience corrosion, movement, or water ingress.

Funnels caused by punching and hammering, vibration, denting caused by loads, and the rotting of purlins...all of these problems are effectively prevented. There is no metal contact between the screw and the sheeting—a polyprop cone acts as an isolator and absorbs contraction and expansion.

The LEAK KING® screw has a special galvanised sleeve that expands as the fastener is screwed in, providing rigid support for the roof sheet and also preventing the fastener from being screwed in too far. The complete screw with sleeve is inserted from above. This prevents indentations, which funnel water on to the purlins. LEAK KING® screws are suitable for IBR and conventional roof sheets, on either metal or timber purlins.

The LEAK KING® screw is an ISO Category 4-compliant screw. From the galvanised washer and sleeve to the polyprop cone, the hot dipped galvanised screw and the poly-isobutyl rubber seal that never becomes brittle or cracks, the LEAK KING® system is corrosion resistant throughout.

The poly-isobutyl rubber seal remains permanently flexible and vulcanises onto the roof sheet and the screw, effectively preventing any leakage. Wood purlins do not get wet and rot, making replacement unnecessary. If correctly installed with butyl sealant and side stitching every 500mm, the roof will be waterproof even in hailstorms when water dams up.

LEAK KING® roof fasteners are being used on various major projects in and around South Africa due to their unique characteristics that make them stand out way above other conventional roof fastening systems. The LEAK KING® system, a South African patent, is suitable for new and existing roofs. LEAK KING® is specified by architects and insisted on by many contractors because they simply do not get any comebacks. So, for watertight peace of mind, insist on LEAK KING® roof fasteners.




LEAK KING
(Pty)Ltd. Reg. No. 75/04189/07

**CSIR
tested and
approved**

**Watertight peace
of mind**





Poly-isobutyl rubber seal that remains permanently flexible and vulcanizes onto the roof sheet and screw effectively preventing any leakage.

No metal contact between screw and sheeting, polyprop cone act as isolator and absorbs contraction and expansion.

Unique underpinning that supports the roof sheet from underneath, adding rigidity to the overall roof structure.

LEAK KING roof fasteners are for all types of roof sheeting. IBR, Corrugated, Fiberglass, Polyethylene and many more. Installed on new and existing roofs

Tel : 014 717 2122
Fax: 086 658 5182
E-mail: info@leakking.co.za
Website: www.leakking.co.za

Factory address: 703 Oktaan Street, industrial Area, Modimolle, 0510, South Africa P O Box 3099, Nylstroom, 0510, RSA

For further information we can be found on Specifile & Klassidex

